

Module	Model	Calendar (programmed to the year)	Illumination	Alarm	Hourly time signal	Snooze feature	Measuring unit (sec.)	Capacity (hours)	Split time	Count-down timer	World time	Dual time	Date display	Battery life (years)	Battery type	Accuracy	Water-resistant to	Additional functions	Page
2711	EF-540D-1A/VEF						1/1	1					•	2	SR927W	± 20	10 bar	Neobrite, screw lock back	12
	EF-540D-5A/VEF																		12
3745	EF-328D-1A/VEF												•	3	SR621SW	± 20	10 bar	Neobrite, date, month, and weekday display, screw lock back	12
	EF-328D-1A5/VEF																		12
	EF-328D-7A/VEF																		12
3745	EF-329D-1A/VEF												•	3	SR621SW	± 20	10 bar	Neobrite, date, month, and weekday display, screw lock back	13
	EF-329D-1A5/VEF																		13
	EF-329D-7A/VEF																		13
4798	EQW-570-1AER	2099	• (AUTO LED)	•			1/100	1				•		2	CR1616	RADIO	10 bar	Radio signal reception (EU), neobrite, velocity indicator	10
5041	EQW-500BE-1A/VER	2099	• (AUTO LED)	•			1/100	2 x 0.5			•			2	CR1616	RADIO	10 bar	Radio signal reception (EU), neobrite	10
5051	EF-534D-1A/VEF						1/1	12					•	2	SR927W	± 20	10 bar	Neobrite, screw lock back	11
	EF-534D-5A/VEF																		11
5061	EQW-M1000SV-1AER	2099		•			1/20	24			•			Solar <sup>1)</sup>	CTL920 <sup>3)</sup>	RADIO	10 bar	Radio signal reception (EU, USA, Japan, China), neobrite, battery level indicator	10
5069	EFE-500D-1A/VEF			•			1/20	24			•			2	SR927W	± 20	10 bar	Neobrite, screw lock back	11
	EFE-500D-7A/VEF																		11
5106	EF-535SVSP-1A/VER						1/1	0.5						2	SR621SW	± 20	10 bar	Neobrite, screw lock crown, screw lock back	10
	EF-535SP-1A/VEF																		11
	EF-535D-7A/VEF																		11
	EF-536D-1A/VEF																		11
5119	EF-539D-1A/VEF						1/1	12					•	2	SR927W	± 20	10 bar	Neobrite, screw lock back	12
	EF-539D-1A5/VEF																		12
	EF-539D-7A/VEF																		12

<sup>1)</sup> up to 20 months of power reserve with power save function switched on; <sup>2)</sup> storage battery

Module	Model	Calendar (programmed to the year)	Illumination	Alarm	Hourly time signal	Measuring unit (sec.)	Capacity (hours)	Split time	Count-down timer	Altimeter	Baro-meter	Thermo-meter	Low-temperature-resistant to (°C)	Battery level indicator	Battery life (years)	Battery type	Accuracy	Water-resistant to	Additional functions	Page
3172	PRW-2000-1ER	2099	• (FULL AUTO EL)	5	•	1/100	24	•					-10	•	Solar <sup>1)</sup>	CTL1616 <sup>3)</sup>	RADIO	10 bar	Radio signal reception (EU, USA, Japan, China), compass, world time, cumulative altitude calculator, data memory, duplex LCD, sunrise/sunset display	13
	PRW-2000T-7ER																			13

<sup>1)</sup> up to 24 months of power reserve with power save function switched on; <sup>2)</sup> storage battery